

Client :	Country :	Quote N° :	00
Full-fill oil transformer			
Number of phases :	<input type="checkbox"/> Single Phase <input type="checkbox"/> Biphasé <input checked="" type="checkbox"/> 3-phases	Dielectric :	<input checked="" type="checkbox"/> Mineral Oil <input type="checkbox"/> Vegetable Oil
INSTALLATION CONDITIONS			
Operation :	<input type="checkbox"/> Step-down <input type="checkbox"/> Step-up	Type :	<input checked="" type="checkbox"/> Cabin H59 <input type="checkbox"/> H61 post
Cooling :	<input checked="" type="checkbox"/> ONAN	Max altitude :	_____ m
Installation :	<input type="checkbox"/> Exterior <input type="checkbox"/> Interior		
Max ambient temp :	<input type="checkbox"/> 40°C <input type="checkbox"/> 45°C <input checked="" type="checkbox"/> 50°C		
ELECTRICAL SPECIFICATIONS			
	Power :	kVA	
	<i>Primary</i>	<i>Secondary</i>	
Voltage :	kV	V	
Primary Voltage settings (%)	<input type="checkbox"/> ±2 x 2.5% <input type="checkbox"/> ±2.5% <input type="checkbox"/> ± 5%		
	Other :		
Highest voltage :	kV	kV	
Power frequency withstand :	kV	kV	
Lightning impulse withstand :	kV		
Short circuit impedance :	% (±10%)		
Nominal current :	A	A	
Type of conductors :	<input type="checkbox"/> Alu <input type="checkbox"/> copper	<input type="checkbox"/> Alu <input type="checkbox"/> Copper	
Coupling :	<input type="checkbox"/> Dyn <input type="checkbox"/> Yzn <input type="checkbox"/> other :		
Hourly index :	<input type="checkbox"/> 11 <input type="checkbox"/> 05 <input type="checkbox"/> other :		
Frequency :	<input type="checkbox"/> 50 Hz <input type="checkbox"/> 60 Hz		
Acoustic power :	dba		
No-load loss :	W	<input type="checkbox"/> +15% <input type="checkbox"/> Max	
Power loss at 75°C :	W	<input type="checkbox"/> +15% <input type="checkbox"/> Max	
CONNECTION			
	<i>Primary</i>	<i>Secondary</i>	
	<input type="checkbox"/> Porcelain terminal <input type="checkbox"/> Plug-in bushing	<input type="checkbox"/> Porcelain terminal <input type="checkbox"/> Bar Pass	
Drain valves :	<input type="checkbox"/> YES <input type="checkbox"/> NO		
OPTINAL ACCESSORIES			
LV IP 315 cover :	<input type="checkbox"/> YES <input type="checkbox"/> NO		
HV lock :	<input type="checkbox"/> YES <input type="checkbox"/> NO		
Protection relay according EN 50216-3 :	<input type="checkbox"/> YES <input type="checkbox"/> NO		

